



DEXTER
LAUNDRY

ON-PREMISE LAUNDRY



6 Cycle Control



30 Cycle Control

T-900 WASHER

Dexter C-Series On-Premise Washer

On-Premise laundry solutions you can depend on.

Dexter C-Series on-premise washers are engineered to show up for work in even the harshest laundry environments. Featuring flexible controls and the same Dexter quality materials and structures our customers have come to trust, each on-premise washer is designed to help you process laundry faster and more efficiently.

When your business depends on clean laundry, choosing the right equipment is an important decision. Our products will provide you the efficiency, flexibility, performance, and durability you need to be confident in your choice. With lifetime technical support and an industry leading 10 year limited warranty, you can be confident that we will stand behind every machine you invest in.

Contact your Dexter Authorized Distributor today for more details.

DURABLE:

With heavy-duty bearings in a cast iron bearing housing, a welded steel spider and shaft, and a rugged frame design that has been proven over two decades, Dexter washers are built to last.

Every model is tested thoroughly with our 1,000 hour out-of-balance test.

The polished chrome doors and AISI 304 stainless steel tub, cylinder, top, front, and side panels keep washers looking great year after year.

RELIABLE:

Our industry leading 10 year warranty covers the frame, tub, cylinder, shaft, seals, bearings, and bearing housing.

A 3 year parts warranty covers the rest.

We stand behind every machine you invest in with lifetime technical support.

EFFICIENT:

Perforated cylinders and raised baffles create superior wash action, while the efficient washer design saves water on every cycle.

The automatic chemical injection feature allows for the perfect combination of chemicals and helps protect your staff from harmful substances.

Standard 100 g-force extraction removes more water and enhances turnover with great wash performance.

INSTALLATION:

Adjustable final extract speeds and other customizable options allow Dexter washers to fit almost any installation.

This Dexter washer fits through a standard 36" doorway.

FLEXIBLE:

The 6 cycle control option provides a flexible and easy to use control with six preset cycles that are programmable to fit your laundry needs.

The 30 cycle control option provides even more power and flexibility with thirty customizable cycles.

The key-lock programming access allows quick access for programming and troubleshooting. This feature is included with both controls options.

OPTIONS:

This model is available with 6 Cycle or 30 cycle programmable controls.

Dexter C-Series 100G washers are available in 20lb, 30lb, 40lb, 60lb, and 80lb capacities.

EMPLOYEE OWNED | MADE IN THE USA | SINCE 1894

DEXTER.COM

2211 WEST GRIMES AVENUE, FAIRFIELD, IOWA 52556 USA

1.800.524.2954

T-900 WASHER SPECIFICATIONS

ON-PREMISE LAUNDRY

Capacity:

Dry Weight Capacity	60 lb	(27.2 kg)
Cylinder Volume	9 cu ft	(254.9 L)

Speed:

High Extract Speed	100 g	(485 RPM)
Intermediate Extract Speed	60 g	(375 RPM)
Washing Speed	0.9 g	(43 RPM)
Motor Size	3 hp	(2.2 kW)

Dimensions:

Cabinet Height	55 3/8"	(140.7 cm)
Cabinet Width	34 3/8"	(87.3 cm)
Cabinet Depth	38 7/8"	(98.8 cm)
Door Opening	19 1/4"	(48.9 cm)
Floor to Door Bottom	16"	(40.6 cm)
Cylinder Diameter	30"	(76.2 cm)
Cylinder Depth	22"	(55.9 cm)

Weight:

Net Weight	1085 lbs	(492.1 kg)
------------	----------	------------

Shipping Information:

Shipping Weight	1115 lbs	(505.8 kg)
Shipping Height	60 3/4"	(154.3 cm)
Shipping Width	36"	(91.4 cm)
Shipping Depth	44 1/4"	(112.4 cm)

Water Requirements:

Water Inlet Size	3/4"	(19 mm)
Flow Rate (per min)	9 gal	(34.1 L)
Pressure (min/max)	30-120 psi	(207-827 kPa)
Drain Diameter (O.D.)	3"	(7.6 cm)
Floor to Center of Drain	6 5/8"	(16.8 cm)


Electrical Requirements:

Model	Volts / Hz / Phase / Wiring	Circuit Breaker / Running Amps / Wire Size
-12	208-240 / 60 / 1 / 2 wire + ground	20 amp / 8.4 amp / #12
-12	208-240 / 60 / 3 / 3 wire + ground	20 amp / 8.4 amp / #12
-39	230 / 50 / 1 / 2 wire + ground	20 amp / 8.4 amp / 3.5 mm ²

Installation Recommendations:

Minimum Clearance Between Machines	1/2"	(1.3 cm)
Minimum Clearance Behind Machines	24"	(61 cm)
Minimum Concrete Thickness	8"	(20.3 cm)

Agency Approvals*



Due to continuous product improvements specifications are subject to change, please consult the installation manual for the most accurate information.
 *Agency approvals may vary depending on the machine configuration, consult Dexter Laundry or your Dexter Authorized Distributor for details.